



## COPPER JOINT 3146

(For use in repairing solvent weld copper connections on copper pipe)

PANEL: Type 304 (18-8) Stainless Steel per ASTM A240.

GASKET: Molded Waffle NBR design from 100% new rubber to ensure performance under varying pressures with superior storage characteristics. Suitable for oil, mild acids, water, salt media and most aliphatic hydrocarbon fluids with a temperature range of -40° to +248°F.

ARMOR PLATE: Type 304 (18-8) Stainless Steel per ASTM A240, bonded to the gasket.

BOLTS & NUTS: Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C111. Optional Stainless Steel materials available with fusion bonded anti-galling coated nuts.

LUGS: Ductile Iron per ASTM A536 with electro galvanized finish.







Nominal Pipe Size		CTS-OD Range		Width		Dord Namehou	Duine Link
Inches	ММ	Inches	MM	Inches	MM	Part Number	Price List
1/2	15	0.625	18	3	80	3146005030WT	\$49.20
3/4	20	0.875	22	3	80	3146007030WT	\$52.50
1	25	1.125	29	3	80	3146010030WT	\$54.20
1 - 1/4	32	1.375	35	3	80	3146012030WT	\$55.80
1- 1/2	40	1.625	41	3	80	3146015030WT	\$59.20
2	50	2.125	54	3	80	3146020030WT	\$66.70
2-1/2	63	2.625	67	3	80	3146025030WT	\$75.00
3	80	3.125	80	3	80	3146030030WT	\$100.80
4	100	4.125	105	3	80	3146030030WT	\$108.30

**HOW TO ORDER:** Specify Model Number and Pipe Size with OD. EXAMPLE: 2" Copper tube O.D. 2.13 with 3" width. Order 3146 - 2.13 x 3. **Part Number:** 3146020030WT