

SINGLE STRAP ALL STAINLESS SADDLE "WIDE RANGE" 3421AS



PANEL & LIFTER BAR: Type 304 (18-8) Stainless Steel per ASTM A240.
BOLTS & NUTS: Type 304 (18-8) Stainless Steel per ASTM A193 and A194. **NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

WASHERS: Delrin per ASTM D6778.

LUGS: Type 304 (18-8) Stainless Steel per ASTM A240.

OUTLET: Type 304 (18-8) Stainless Steel per ASTM A276.

GASKET: NBR per ASTM D2000; Mat gasket with patented TwinSeal® dual o-ring design incorporating both hydrostatic and mechanical forces to affect a dynamic seal, with a temperature range of -25°F to +248°F.

BODY WIDTH: 4". . **STRAP WIDTH:** 2".

Nominal Pipe Size		Letter	Pipe OD Range		Part number	Outlet Size / List price
Inches	MM		Inches	MM		3/4 CC - 3/4 NPT 1 CC - 1 NPT
4	100	A	4.35-5.65	111-144	342104A+Outlet size+T+Code	\$174.30
5	125	A	5.40-6.40	137-163	342105A+Outlet size+T+Code	\$177.90
6	150	A	6.45-7.75	164-197	342106A+Outlet size+T+Code	\$183.00
8	200	A	8.50-9.80	216-249	342108A+Outlet size+T+Code	\$187.00
10	250	A	10.25-11.55	260-293	342110A+Outlet size+T+Code	\$224.10
		B	10.95-12.35	278-314	342110B+Outlet size+T+Code	\$224.10
12	300	A	12.30-13.60	312-345	342112A+Outlet size+T+Code	\$230.40
		B	13.14-14.44	334-367	342112B+Outlet size+T+Code	\$230.40



HOW TO ORDER: Choose nominal pipe sizes x outlet size and thread configuration.

EXAMPLE: 12" ductile iron pipe with a 1" CC tap. Order 3421AS-12A x 1CC. **Part Number:** 342112A100TD.

NOTE: Other ranges, tap sizes available upon request.

Outlet	Outlet size	Thread standard	Outlet code
3/4	075	NPT	C
		CC	B
1	100	NPT	E
		CC	D
1 1/4	125	NPT	G
		CC	F
1 1/2	150	NPT	I
		CC	H
2	200	NPT	K
		CC	J

IP = NPT CC=AWWA