

# LONG BARREL POWERMAX COUPLING 3506LB



**One range fits all pipe ODs IPS PVC to Rough Barrel AC**  
**CENTER BARREL:** Ductile Iron per ASTM A536 and AWWA C219.

**GLANDS:** Ductile Iron per ASTM A536 and AWWA C219.

**GASKET:** SBR per ASTM D2000 with conical design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -40° to +200° F. Other materials available.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219. Type 304 (18-8) Stainless Steel per ASTM A193 and A194. Type 316 available.

**FINISH:** Epoxy.



**MEETS  
AWWA  
C219**



Nominal Pipe Size			Pipe OD Range		Long Barrel Weight		Long Barrel Length		Long Barrel Part Number	List Price	Long Barrel Part Number w/SST N&Bs	List Price w/SST N&Bs
Inches	MM	A	Inches	MM	lbs	kgs	Inches	MM				
2	50	A	2.30-2.90	58-74	22	10	12	300	350602A000LB	\$262.60	350602A0SSLB	\$323.50
3	80	A	3.40-4.20	86-107	33	15	12	300	350603A000LB	\$416.50	350603A0SSLB	\$496.80
4*	100	A	4.20-5.33	107-135	37	17	12	300	350604A000LB	\$500.40	350604A0SSLB	\$628.00
6*	150	A	6.25-7.45	159-189	50	23	12	300	350606A000LB	\$658.10	350606A0SSLB	\$817.60
8*	200	A	8.40-9.79	214-249	73	33	12	300	350608A000LB	\$771.80	350608A0SSLB	\$963.20
10	250	A	10.70-12.12	272-308	77	35	12	300	350610A000LB	\$933.90	350610A0SSLB	\$1,125.30
12	300	A	12.75-14.38	324-365	113	51	12	300	350612A000LB	\$1,087.80	350612A0SSLB	\$1,357.80



# ALL SS POWERMAX COUPLING 3506AS

**CENTER BARREL:** Type 304 (18-8) Stainless Steel per ASTM A240.

**GLANDS:** Type 304 (18-8) Stainless Steel per ASTM A743.

**GASKET:** SBR per ASTM D2000 with conical design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -40° to +200° F. Other materials available.

**BOLTS & NUTS:** Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

Type 316 available.

**NOTE:** Hex nuts are furnished to prevent seizing and galling.



**MEETS  
AWWA  
C219**



Nominal Pipe Size			Pipe OD Range		Approx. Weight		Barrel Length		Bolts	Part Number	List Price
Inches	MM	A	Inches	MM	lbs	kgs	Inches	MM	Qty		
2	50	A	2.30-2.90	58-74	11	5	5	125	2	350602A000AS	\$528.80
3	80	A	3.40-4.20	86-107	14	6.5	6.5	165	3	350603A000AS	\$581.20
4*	100	A	4.20-5.33	112-135	18	8.5	6	150	4	350604A000AS	\$719.50
6*	150	A	6.25-7.45	166-189	24	11	6	150	5	350606A000AS	\$979.50
8*	200	A	8.40-9.79	217-249	40	16.5	10	250	6	350608A000AS	\$1,454.00
10	250	A	10.70-12.12	272-293	46	21	10	250	7	350610A000AS	\$2,107.40
12	300	A	12.75-14.38	324-365	56	25.5	10	250	8	350612A000AS	\$2,463.80

**Note:** Protection against possible pull out of pipe ends is not provided with cast couplings unless pipe is restrained. \*Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure. **HOW TO ORDER:** Specify model number, pipe size with letter code(s) if applicable. **EXAMPLE:** 6" Steel O.D. 6.63 to 6" Asbestos cement O.D. 7.37 order 3506AS-6A. **Part number:** 350606A000AS.