

3121AS-LW ALL STAINLESS SEWER CLAMP

PANEL & LIFTER BAR: Type 304 (18-8) Stainless Steel per ASTM A240.

GASKET: SBR Chek-O-Seal with multi o-ring sealing ribs from 100% new rubber to ensure performance under varying pressures with superior storage characteristics. Suitable for mild acids, water and salt media with a temperature range of -25°F to +200°F per ASTM D2000 . Other materials available.

ARMOR PLATE: Type 304 (18-8) Stainless Steel per ASTM A240, recessed and bonded to the gasket.

BOLTS & NUTS: Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

NOTE: Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

LUGS: Type 304 (18-8) Stainless Steel per ASTM A240.

WASHERS: Delrin per MIL-A50424.

MEETS AWWA C230



Nominal Pipe Size		Pipe OD Range		Width		Part Number	List Price
Inches	MM	Inches	MM	Inches	MM		
2 A	50	2.37-2.63	60-67	6	150	312102A060LW	\$ 97.00
				8	200	312102A080LW	\$ 132.90
				12	300	312102A120LW	\$ 221.30
2 B	50	2.62-2.87	67-73	6	150	312102B060LW	\$ 97.00
				8	200	312102B080LW	\$ 132.90
				12	300	312102B120LW	\$ 221.30
2 C	50	2.87-3.12	73-79	6	150	312102C060LW	\$ 97.00
				8	200	312102C080LW	\$ 132.90
				12	300	312102C120LW	\$ 221.30
3 A	80	3.45-3.70	88-94	6	150	312103A060LW	\$ 117.40
				8	200	312103A080LW	\$ 144.90
				12	300	312103A120LW	\$ 234.30
3 B	80	3.75-4.00	95-102	6	150	312103B060LW	\$ 117.40
				8	200	312103B080LW	\$ 144.90
				12	300	312103B120LW	\$ 234.30
3 C	80	3.95-4.20	100-107	6	150	312103C060LW	\$ 117.40
				8	200	312103C080LW	\$ 144.90
				12	300	312103C120LW	\$ 234.30
4 A	100	4.45 - 4.75	113-121	6	150	312104A060LW	\$ 131.00
				8	200	312104A080LW	\$ 163.60
				12	300	312104A120LW	\$ 259.80
4 B	100	4.74 - 5.14	120-131	6	150	312104B060LW	\$ 131.00
				8	200	312104B080LW	\$ 163.60
				12	300	312104B120LW	\$ 259.80
4 C	100	4.95-5.35	126-136	6	150	312104C060LW	\$ 131.00
				8	200	312104C080LW	\$ 163.60
				12	300	312104C120LW	\$ 259.80

3121AS-LW ALL STAINLESS SEWER CLAMP

Nominal Pipe Size		Pipe OD Range		Width		Part Number	List Price
Inches	MM	Inches	MM	Inches	MM		
4D	100	5.20-5.60	132-142	6	150	312104D060LW	\$ 131.00
				8	200	312104D080LW	\$ 163.60
				12	300	312104D120LW	\$ 259.80
6A	150	5.95 - 6.35	151 - 161	6	150	312106A060LW	\$ 162.00
				8	200	312106A080LW	\$ 195.20
				12	300	312106A120LW	\$ 312.60
6B	150	6.60 - 7.00	168-178	6	150	312106B060LW	\$ 162.00
				8	200	312106B080LW	\$ 195.20
				12	300	312106B120LW	\$ 313.00
6C	150	6.84 - 7.24	174 - 184	6	150	312106C060LW	\$ 162.00
				8	200	312106C080LW	\$ 195.00
				12	300	312106C120LW	\$ 312.60
6D	150	7.05 - 7.46	179 - 189	6	150	312106D060LW	\$ 162.00
				8	200	312106D080LW	\$ 195.20
				12	300	312106D120LW	\$ 312.60
6E	150	7.40-7.80	188 - 198	6	150	312106E060LW	\$ 162.00
				8	200	312106E080LW	\$ 195.20
				12	300	312106E120LW	\$ 312.60
8A	200	7.95 - 8.35	202 - 212	6	150	312108A060LW	\$ 191.70
				8	200	312108A080LW	\$ 229.30
				12	300	312108A120LW	\$ 368.10
8B	200	8.60 - 9.00	218-229	6	150	312108B060LW	\$ 191.70
				8	200	312108B080LW	\$ 229.30
				12	300	312108B120LW	\$ 368.10
8C	200	9.00-9.40	229-239	6	150	312108C060LW	\$ 191.70
				8	200	312108C080LW	\$ 229.30
				12	300	312108C120LW	\$ 368.10
8D	200	9.30-9.70	236-246	6	150	312108D060LW	\$ 191.70
				8	200	312108D080LW	\$ 229.30
				12	300	312108D120LW	\$ 368.10

MANUFACTURERS RECOMMENDATIONS

- Clamp width should equal or exceed pipe diameter for higher working pressures.
- Repair Clamps are not recommended for use in joining plain end pressure pipe.
- Other sizes and widths not listed are readily available. Price on request.

Pipe OD Range = 0.40" (10mm) Pipe Sizes 1 1/4 through 6 inch are available in 6 inch Width and are priced the same as the 8 inch Width. See product 3131AS for Tapped Outlets.

HOW TO ORDER: Specify Model Number, Pipe Size with Letter Code, and Width. EXAMPLE: 6" SDR 35 PVC O.D. 6.28 with 8" Clamp Width. Order 3121AS-LW - 6A x 8. **Part Number:** 312106A080LW .

NOTE 1: Clamps will not eliminate axial / lateral movement of pipe. Some type of pipe restraint or anchoring product must be used in these situations.

NOTE 2: When clamps are used on HDPE you must use spring washers. See HDPE products section.