

## 3146 POWERCOPPER JOINT REPAIR CLAMP

(For use in repairing solvent weld copper connections on copper pipe)

**PANEL:** Type 304 (18-8) Stainless Steel per ASTM A240.

**GASKET:** Molded Waffle NBR design from 100% new rubber to ensure performance under varying pressures with superior storage characteristics. Suitable for oil, mild acids, water, salt media and most aliphatic hydrocarbon fluids with a temperature range of -25° to +248°F.

**ARMOR PLATE:** Type 304 (18-8) Stainless Steel per ASTM A240, bonded to the gasket.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C111. Optional Stainless Steel materials available with fusion bonded anti-galling coated nuts.

**LUGS:** Ductile Iron per ASTM A536 with electro galvanized finish.



Nominal Pipe Size		CTS-OD Range		Width		Part Number	Price List
Inches	MM	Inches	MM	Inches	MM		
1/2	15	0.625	18	3	80	3146005030WT	\$ 29.50
3/4	20	0.875	22	3	80	3146007030WT	\$ 31.50
1	25	1.125	29	3	80	3146010030WT	\$ 32.50
1 - 1/4	32	1.375	35	3	80	3146012030WT	\$ 33.50
1 - 1/2	40	1.625	41	3	80	3146015030WT	\$ 35.50
2	50	2.125	54	3	80	3146020030WT	\$ 40.00
2-1/2	63	2.625	67	3	80	3146025030WT	\$ 45.00
3	80	3.125	80	3	80	3146030030WT	\$ 60.50
4	100	4.125	105	3	80	3146030030WT	\$ 65.00

**HOW TO ORDER:** Specify Model Number and Pipe Size with OD. EXAMPLE: 2" Copper tube O.D. 2.13 with 3" width. Order 3146 - 2.13 x 3. **Part Number:** 3146020030WT