

### 3202 / 3202LB SPLIT SLEEVE REPAIR CLAMP

**BODY CASTING:** Ductile Iron per ASTM A536.  
**GASKET:** SBR per ASTM D2000.  
**BOLTS & NUTS:** Low Alloy Steel per ASTM A325 AND ASTM A563.  
**FINISH:** Epoxy.



3202		Pipe OD Range		Approx Weight		Part Number	List Price	
Inches	MM	Inches	MM	lbs.	kgs.			
6	150	6.84 - 6.96	174-177	34	15	320206000000	Standard	\$ 444.90
						32020600000C	Tapped	\$ 541.90
3202 LB								
6	150	6.84 - 6.96	174-177	75	34	320206LB0000	Standard	\$ 988.60
						320206LB000C	Tapped	\$ 1,085.60
3202								
8	200	8.99-9.11	228-231	44	20	320208000000	Standard	\$ 549.60
						32020800000C	Tapped	\$ 646.30
3202 LB								
8	200	8.99-9.11	228-231	90	41	320208LB0000	Standard	\$ 1,221.10
						320208LB000C	Tapped	\$ 1,318.10

The Standard unit is also available with a 3/4" NPT / CC Tapped Outlet and Plug for venting purposes.

**HOW TO ORDER:** Specify Model Number, and Pipe Size. EXAMPLE: 6" Standard Split Sleeve Repair Clamp.  
 Order 3202-6" **Part Number:** 320206000000.

**MORE INFORMATION:** The Split Sleeve Repair Clamp has been reintroduced (formerly the Clow Model F1202) for those customers who need a rugged heavy duty repair sleeve for Ductile and Cast Iron pipe. This ductile iron bodied fitting is strong enough to realign offset and deflected pipe that has a circumferential break.