

3202 / 3202LB

SPLIT SLEEVE REPAIR CLAMP

BODY CASTING: Ductile Iron per ASTM A536.

GASKET: SBR per ASTM D2000.

BOLTS & NUTS: Low Alloy Steel per ASTM A325
AND ASTM A563.

FINISH: Epoxy.



MEETS
AWWA
C230

	Nominal Pipe Size		Pipe OD Range		Approx Weight		Part Number	List Price	
	Inches	MM	Inches	MM	lbs.	kgs.			
3202	6	150	6.84 - 6.96	174-177	34	15	320206000000	Standard	\$741.50
							32020600000C	Tapped	\$903.20
	6	150	6.84 - 6.96	174-177	75	34	320206LB0000	Standard	\$1,647.70
							320206LB000C	Tapped	\$1,809.30
3202LB	8	200	8.99-9.11	228-231	44	20	320208000000	Standard	\$916.00
							32020800000C	Tapped	\$1,077.20
	8	200	8.99-9.11	228-231	90	41	320208LB0000	Standard	\$2,035.20
							320208LB000C	Tapped	\$2,196.80

The Standard unit is also available with a 3/4" NPT / CC Tapped Outlet and Plug for venting purposes.

HOW TO ORDER: Specify Model Number, and Pipe Size. EXAMPLE: 6" Standard Split Sleeve Repair Clamp. Order 3202-6"
Part Number: 320206000000.

MORE INFORMATION: The Split Sleeve Repair Clamp has been reintroduced (formerly the Clow Model F1202) for those customers who need a rugged heavy duty repair sleeve for Ductile and Cast Iron pipe. This ductile iron bodied fitting is strong enough to realign offset and deflected pipe that has a circumferential break.