3412AS-PE/

ALL STAINLESS SADDLE - DOUBLE STUD BOLT DESIGN

PANEL & LIFTER BAR: TType 304 (18-8) Stainless Steel per ASTM A240.
BOLTS & NUTS: Type 304 (18-8) Stainless Steel per ASTM A193 and A194. NOTE: Hex nuts are furnished with fusion bonded coating to prevent seizing and galling.
WASHERS: Stainless Steel per ASTM A240, type 304. Special spring type.
LUGS: TType 304 (18-8) Stainless Steel per ASTM A240.
OUTLET: Type 304 (18-8) Stainless Steel per ASTM A276
GASKET: NBR per ASTM D2000; Patented TwinSeal® dual o-ring design incorporating both hydrostatic and mechanical forces to affect a dynamic seal.



Made in U.S.A

MEETS AWWA **C230**

Nominal Pipe Size	Pipe OD Range		Model 3412AS-PE		Part number
			Outlet Size / List price		
Inches	Inches	MM	3/4 CC - 3/4 NPT 1 CC - 1 NPT	1 1/4 CC - 1 1/4 NPT 1 1/2 CC - 1 1/2 NPT 2 CC - 2 NPT	
3	3.48-3.52	88-90	$430.70	$494.80	
4	4.50-4.80	114-122	$442.30	$494.80	
5	5.54-5.84	141-148	$463.80	$542.00	3412+Nominal pipe size+Outlet size+T+ Outlet Code +(-PE)
6	6.63-6.90	168-175	$516.90	$553.60	
8	8.63-9.05	219-230	$556.90	$604.60	
10	10.75-11.10	273-282	$791.60	$864.70	
12	12.75-13.20	324-335	$791.60	$864.70	

HOW TO ORDER: Choose nominal pipe size x outlet size and thread configuration. **Part Number:** 3412+Nominal pipe size+Outlet size+T+Outlet Code+(-PE), 3412040075TB-PE .

OUTLET CODE													
Outlet	3/4		1		1 1/4		1 1/2		2		2 1/2	3	4
Outlet size	075		100		125		150		200		250	300	400
Thread standard	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	NPT	NPT
Outlet code	C	B	E	D	G	F	I	H	K	J	N	P	M

IP = NPT CC=AWWA