

3417SW

DUCTILE IRON SADDLE WITH SINGLE WIDE STRAP



BODY CASTING: Ductile Iron per ASTM A536.
STRAP: Type 304 (18-8) Stainless Steel per ASTM A240.
STUD BOLTS: Type 304 (18-8) Stainless Steel per ASTM A193.
NUTS: Type 304 (18-8) Stainless Steel per ASTM A194. **NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.
GASKET: NBR per ASTM D2000 with Unique dual O-Ring design permanently bonded in recessed casting, with a temperature range of -40°F to +248°F.
FINISH: Epoxy.

Nominal Pipe Size		Letter	Pipe OD Range		Part number	Outlet Size / List price	
Inches	MM		Inches	MM		1/2 NPT 3/4 CC - 3/4 NPT 1 CC - 1 NPT	1 1/4 CC - 1 1/4 NPT 1 1/2 CC - 1 1/2 NPT 2 CC - 2 NPT
2*	50	A	2.38-2.50	61-64	341702A+Outlet size+H+Code+(-SW)	\$175.50	\$190.30
3*	80	A	3.50	89	341703A+Outlet size+H+Code+(-SW)	\$175.80	\$202.00
		B	3.45-4.05	89-103	341703B+Outlet size+H+Code+(-SW)		
4	100	A	4.00-4.50	102-114	341704A+Outlet size+H+Code+(-SW)	\$176.90	N/A
		B	4.74-5.63	120-143	341704B+Outlet size+H+Code+(-SW)		
		C	4.74-5.14	120-131	341704C+Outlet size+H+Code+(-SW)		
6	150	A	6.00-6.63	152-168	341706A+Outlet size+H+Code+(-SW)	\$199.20	\$224.40
		B	6.84-7.64	174-194	341706B+Outlet size+H+Code+(-SW)		
		C	6.63-6.90	168-175	341706C+Outlet size+H+Code+(-SW)		
8	200	A	8.00-8.63	203-219	341708A+Outlet size+H+Code+(-SW)	\$241.60	\$278.10
		B	8.54-10.10	216-257	341708B+Outlet size+H+Code+(-SW)		
		C	8.63-9.05	219-229	341708C+Outlet size+H+Code+(-SW)		
10	250	A	10.00-11.10	254-282	341710A+Outlet size+H+Code+(-SW)	\$335.50	\$335.70
		B	10.64-12.12	270-308	341710B+Outlet size+H+Code+(-SW)		
12	300	A	12.00-13.20	305-335	341712A+Outlet size+H+Code+(-SW)	\$340.30	\$388.90
		B	12.62-14.32	321-364	341712B+Outlet size+H+Code+(-SW)		
12-14	300-350	A	14.73-15.65	374-398	34171214+Outlet size+H+Code+(-SW)	\$407.30	\$412.00
16-18	400-450	A	17.40-18.88	442-480	341716A+Outlet size+H+Code+(-SW)	\$415.00	\$465.80
18	450	A	19.50	495	341718A+Outlet size+H+Code+(-SW)	\$638.10	\$678.30
20	500	A	21.60	549	341720A+Outlet size+H+Code+(-SW)	\$714.50	\$757.50
24	600	A	25.80	655	341724A+Outlet size+H+Code+(-SW)	\$840.40	\$890.70

HOW TO ORDER: Choose nominal pipe size x outlet size and thread configuration. **EXAMPLE:** 4" Ductile Iron O.D. 4.80 with 3/4 CC outlet. Order 3417SW - 4B x 3/4 CC. **Part Number:** 341704B075HB-SW . **NOTE:** Please advise when saddles are being ordered for use on C900 pipe.

OUTLET CODE PART CHART

Outlet	3/4		1		1 1/4		1 1/2		2		2 1/2		3		4	
Outlet size	075		100		125		150		200		250		300		400	
Thread standard	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC
Outlet code	C	B	E	D	G	F	I	H	K	J	N	P	M			

IP = NPT CC=AWWA

*Available in 1.25 CC/NPT + 1.5 NPT.