

3421AS SINGLE STRAP ALL STAINLESS SADDLE "WIDE RANGE"



PANEL & LIFTER BAR: Type 304 (18-8) Stainless Steel per ASTM A240.

BOLTS & NUTS: Type 304 (18-8) Stainless Steel per ASTM A193 and A194. **NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

WASHERS: Delrin per ASTM D6778.

LUGS: Type 304 (18-8) Stainless Steel per ASTM A240.

OUTLET: Type 304 (18-8) Stainless Steel per ASTM A276.

GASKET: NBR per ASTM D2000; Mat gasket with patented TwinSeal® dual o-ring design incorporating both hydrostatic and mechanical forces to affect a dynamic seal, with a temperature range of -25°F to +248°F.

BODY WIDTH: 4".

STRAP WIDTH: 2".

Nominal Pipe Size		Clamp OD Range		Letter code	Outlet Size	Part Number	List Price
Inches	MM	Inches	MM				
4	100	4.35 - 5.65	111 - 144	A	3/4 CC	342104A075TB	\$ 139.50
					3/4 NPT	342104A075TC	
					1 CC	342104A100TD	
					1 NPT	342104A100TE	
5	125	5.40 - 6.40	137 - 163	A	3/4 CC	342105A075TB	\$ 142.30
					3/4 NPT	342105A075TC	
					1 CC	342105A100TD	
					1 NPT	342105A100TE	
6	150	6.45 - 7.75	164 - 197	A	3/4 CC	342106A075TB	\$ 146.40
					3/4 NPT	342106A075TC	
					1 CC	342106A100TD	
					1 NPT	342106A100TE	
8	200	8.50 - 9.80	216 - 249	A	3/4 CC	342108A075TB	\$ 149.60
					3/4 NPT	342108A075TC	
					1 CC	342108A100TD	
					1 NPT	342108A100TE	
10	250	10.25 - 11.55	260 - 293	A	3/4 CC	342110A075TB	\$ 179.30
					3/4 NPT	342110A075TC	
					1 CC	342110A100TD	
					1 NPT	342110A100TE	
		10.95 - 12.35	278 - 314	B	3/4 CC	342110B075TB	
					3/4 NPT	342110B075TC	
					1 CC	342110B100TD	
					1 NPT	342110B100TE	
12	300	12.30 - 13.60	312 - 345	A	3/4 CC	342112A075TB	\$ 184.30
					3/4 NPT	342112A075TC	
					1 CC	342112A100TD	
					1 NPT	342112A100TE	
		13.14 - 14.44	334-367	B	3/4 CC	342112B075TB	
					3/4 IP	342112B075TC	
					1 CC	342112B100TD	
					1 NPT	342112B100TE	

HOW TO ORDER: Choose nominal pipe sizes x outlet size and thread configuration.

EXAMPLE: 12" ductile iron pipe with a 1" CC tap. Order 3421AS-12A x 1CC. **Part Number:** 342112A100TD.

NOTE: Other ranges, tap sizes available upon request.