

3506AS ALL SS POWERMAX COUPLING

CENTER BARREL: Type 304 (18-8) Stainless Steel per ASTM A240.

GLANDS: Type 304 (18-8) Stainless Steel per ASTM A743.

GASKET: SBR per ASTM D2000 with conical design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -25° to +200° F. Other materials available.

BOLTS & NUTS: Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

NOTE: Hex nuts are furnished to prevent seizing and galling.



Nominal Pipe Size			Pipe OD Range		Approx. Weight		Barrel Length		Bolts	Part Number	List Price
Inches	MM		Inches	MM	lbs	kgs	Inches	MM	Qty		
2	50	A	2.30-2.90	58-74	11	5	5	125	2	350602A000AS	\$ 306.70
3	80	A	3.40-4.20	86-107	14	6.5	6.5	165	3	350603A000AS	\$ 337.40
4*	100	A	4.20-5.33	112-135	18	8.5	6	150	4	350604A000AS	\$ 417.30
6*	150	A	6.25-7.45	166-189	24	11	6	150	5	350606A000AS	\$ 568.10
8*	200	A	8.40-9.79	217-249	40	16.5	10	250	6	350608A000AS	\$ 843.30
10	250	A	10.70-12.12	272-293	46	21	10	250	7	350610A000AS	\$ 1,222.30
12	300	A	12.75-14.38	324-345	56	25.5	10	250	8	350612A000AS	\$ 1,429.00

Note: Protection against possible pull out of pipe ends is not provided with cast couplings unless pipe is restrained.

*Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure.

HOW TO ORDER: Specify Model Number, Pipe Size with Letter Code(s) if applicable. **EXAMPLE:** 6" Steel O.D. 6.63 to 6" Asbestos Cement O.D. 7.37. Order 3506AS - 6A. **Part Number:** 350606A000AS .