

3506EC ENDCAP POWERMAX COUPLING

One range fits all pipe ODs IPS PVC to Rough Barrel AC

The EndCap Coupling is used to Dead End a pipeline permanently or for test purposes. The 2" NPT plugged outlet can be oriented at the top to vent air or rotated to the bottom of the coupling to function as a drain.

CENTER BARREL: Ductile Iron per ASTM A536 and AWWA C219.

GASKET: SBR per ASTM D2000 with conical design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -25° to +200° F.

BOLTS & NUTS: Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219. Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

GLANDS: Ductile Iron per ASTM A536 and AWWA C219.

END CAP: Ductile Iron per ASTM A536 and AWWA C219.

FINISH: Epoxy.



Nominal Pipe Size			Pipe OD Range		Standard Weight		Standard Barrel Length		Standard Barrel Part Number	List Price	Standard Barrel Part Number w/SST N&Bs	List Price w/SST N&Bs	
Inches	MM		Inches	MM	lbs	kgs	Inches	MM					
2	50	A	2.30-2.90	58-74	CONSULT FACTORY			5	125	350602A000EC	\$ 140.40	350602A0SSEC	\$ 210.80
3	80	A	3.40-4.20	86-107				5	125	350603A000EC	\$ 205.10	350603A0SSEC	\$ 308.50
4*	100	A	4.20-5.33	107-135				6	150	350604A000EC	\$ 235.10	350604A0SSEC	\$ 366.90
6*	150	A	6.25-7.45	159-189				6	150	350606A000EC	\$ 334.60	350606A0SSEC	\$ 512.80
8*	200	A	8.40-9.79	214-249				10	250	350608A000EC	\$ 411.20	350608A0SSEC	\$ 635.00
10	250	A	10.70-12.12	272-308				10	250	350610A000EC	\$ 647.20	350610A0SSEC	\$ 949.80
12	300	A	12.75-14.38	324-365				10	250	350612A000EC	\$ 940.30	350612A0SSEC	\$ 1,180.50
14	350	A	15.25-16.90	387-429				12	300	350614A000EC	\$ 969.50	350614A0SSEC	\$ 1,209.70
16	400	A	16.00-17.80	406-452				12	300	350616A000EC	\$ 3,143.70	350616A0SSEC	\$ 4,198.40
		B	17.40-19.00	442-483				12	300	350616B000EC	\$ 3,143.70	350616B0SSEC	\$ 4,198.40

Note: Protection against possible pull out of pipe ends is not provided with cast couplings unless pipe is restrained.

* Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure.

HOW TO ORDER: Specify Model Number, Pipe Size with Letter Code(s) if applicable. **EXAMPLE:** 6" Steel O.D. 6.63. Order 3506EC - 6A. **Part Number:** 350606A000EC .



COATING OPTION: Anti-Seizing/Galling protection. Available for both Alloy and SST application. Inquire with sales for cost and availability.