

## MODEL 3506R POWERMAX REDUCING COUPLING

**CENTER BARREL:** Ductile Iron per ASTM A536 and AWWA C219.

**GLANDS:** Ductile Iron per ASTM A536 and AWWA C219.

**GASKET:** SBR per ASTM D2000 with conical design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -25° to +200° F.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219./Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

**FINISH:** Epoxy.



Nominal Pipe Size		Pipe OD Ranges Other End		Pipe OD Ranges Other End		Part Number	List Price	Part Number	List Price w/SST N&Bs	Weight		Barrel Length	
Inches	MM	Inches	MM	Inches	MM					lbs	kgs	Inches	MM
4x3	100x75	4.20-5.33	107-135	3.40-4.20	86-107	35060400300R	\$ 256.90	350604003SSR	\$ 299.90	40	18	12	300
6x4	150x100	6.25-7.45	159-789	4.20-5.33	107-135	35060600400R	\$ 337.80	350606004SSR	\$ 391.50	50	23	12	300
8x6	200x150	8.40-9.79	214-249	6.25-7.45	159-789	35060800600R	\$ 433.00	350608006SSR	\$ 497.40	64	29	12	300
10x8	250x200	10.45-12.12	272-308	8.40-9.79	214-249	35061000800R	\$ 610.30	350610008SSR	\$ 697.50	98	45	16	400
12x10	300x250	12.50-14.38	324-365	10.45-12.12	272-308	35061201000R	\$ 821.40	350612010SSR	\$ 897.30	134	61	16	400

**Note:** Protection against possible pull out of pipe ends is not provided with cast couplings unless pipe is restrained. Pipe diameters less than IPS/STEEL rated up to 50 psi work pressure.

**HOW TO ORDER:** Specify Model Number, Pipe Sizes. **EXAMPLE:** 8" Asbestos Cement OD 9.37 to 6" C900 OD 6.90, order 3506R-8x6. **Part Number:** 35060800600R .