

# 3415AS

## STAINLESS SADDLE SINGLE STRAP

(CAST ALL STAINLESS STEEL BODY)

**BODY CASTING:** Stainless steel 18-8 ASTM A743

**STRAP:** Type 304 (18-8) Stainless steel per ASTM A240

**STUD BOLTS:** Type 304 (18-8) Stainless steel per ASTM A193

**NUTS:** Type 304 (18-8) Stainless steel per ASTM A194. NOTE: Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

**GASKET:** NBR per ASTM D2000; Patented Twinseal dual o-ring design incorporating both hydrostatic and mechanical forces to affect a dynamic seal, with a temperature range of -40°F to +248°F.



Made in U.S.A

MEETS  
AWWA  
C800



Nominal Pipe Size		Pipe OD Range		Part number	Outlet Size / List price	
Inches	MM	Inches	MM		1/2 CC - 1/2 NPT 3/4 CC - 3/4 NPT 1 CC - 1 NPT	1 1/4 CC - 1 1/4 NPT 1 1/2 CC - 1 1/2 NPT 2 CC - 2 NPT
3-4	80-100	3.74-4.55	95-116	3415034+Outlet size+H+Code+AS	\$303.70	N/A
4-5	100-125	4.74-5.63	120-143	3415040+Outlet size+H+Code+AS	\$305.30	\$491.00
5-6	125-150	5.94-6.70	151-170	3415056+Outlet size+H+Code+AS	\$311.80	\$525.30
6	150	6.84-7.60	174-193	3415060+Outlet size+H+Code+AS	\$313.50	\$536.80
6C	150	6.63-6.90	168-175	341506C+Outlet size+H+Code+AS	\$339.50	\$536.80
6-8	150-200	7.69-8.72	195-222	3415068+Outlet size+H+Code+AS	\$340.80	\$540.50
8A	200	8.63-9.05	219-229	341508A+Outlet size+H+Code+AS	\$344.30	\$554.20
8-10	200-250	8.54-10.10	217-257	3415080+Outlet size+H+Code+AS	\$353.20	\$578.50
10-12	250-300	10.64-12.12	270-308	3415100+Outlet size+H+Code+AS	\$391.20	\$608.70
12-14	300-350	12.62-14.32	321-364	3415120+Outlet size+H+Code+AS	\$421.50	\$656.20

**HOW TO ORDER:** Choose nominal pipe size x outlet size and thread configuration.

**EXAMPLE:** 4" Ductile Iron O.D. 4.80 with 3/4 CC outlet. Order 3415AS 4-5 x 3/4 CC.

**Part Number:** 3415040075HB-AS

**NOTE:** Please advise when saddles are being ordered for use on C900 pipe.

**MANUFACTURER SUGGESTION:** For PVC pipe applications, order saddle which has OD of pipe at the top of range.

Outlet	Outlet size	Thread standard	Outlet code
3/4	075	NPT	C
		CC	B
1	100	NPT	E
		CC	D
1 1/4	125	NPT	G
		CC	F
1 1/2	150	NPT	I
		CC	H
2	200	NPT	K
		CC	J

IP = NPT CC=AWWA