3233A/C

COUPLING LEAK REPAIR CLAMP

FOR CLASS 150 PIPE

CASTINGS: Ductile Iron per ASTM A536.

GASKET: NBR produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics. Suitable for oil, mild acids, water, salt media and most aliphatic hydrocarbon fluids with a temperature range of -40°F to +248°F.

BOLTS & NUTS: Low alloy Steel per ASTM A325 and ASTM A563.

FINISH: Epoxy.









Nominal Pipe Size		Pipe OD Range		Approx Weight		Part Number	Price A/C	Gasket part number	Price Additional
Inches	MM	Inches	MM	lbs.	kgs.	Fait Nullibel	Coupling	dasket part number	Gasket
4	100	5.07-5.20	129-132	25	11	3233040000HA	\$488.80	V3233041	\$71.30
6	150	7.17-7.35	182-187	32	15	3233060000HA	\$561.70	V3233061	\$88.70
8	200	9.37-9.50	238-241	37	17	3233080000HA	\$729.70	V3233081	\$110.70

NOTE: This repair clamp is furnished with one gasket. If both ends of the A/C Coupling are leaking order one additional gasket.

HOW TO ORDER: Specify Model

Number, and Pipe Size.

EXAMPLE: 8" 3233 A/C Coupling Leak Repair Clamp . Order 3233-8. **Part Number:** 3233080000HA .

