

3415AS

STAINLESS SADDLE SINGLE STRAP

(CAST ALL STAINLESS STEEL BODY)

BODY CASTING: Stainless steel 18-8 ASTM A743

STRAP: Type 304 (18-8) Stainless steel per ASTM A240

STUD BOLTS: Type 304 (18-8) Stainless steel per ASTM A193

NUTS: Type 304 (18-8) Stainless steel per ASTM A194. NOTE: Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

GASKET: NBR per ASTM D2000; Patented Twinseal dual o-ring design incorporating both hydrostatic and mechanical forces to affect a dynamic seal, with a temperature range of -40°F to +248°F.



Made in U.S.A

MEETS
AWWA
C800



Nominal Pipe Size		Pipe OD Range		Part number	Outlet Size / List price	
Inches	MM	Inches	MM		1/2 CC - 1/2 NPT 3/4 CC - 3/4 NPT 1 CC - 1 NPT	1 1/4 CC - 1 1/4 NPT 1 1/2 CC - 1 1/2 NPT 2 CC - 2 NPT
3-4	80-100	3.74-4.55	95-116		\$303.70	N/A
4-5	100-125	4.74-5.63	120-143		\$305.30	\$491.00
5-6	125-150	5.94-6.70	151-170		\$311.80	\$525.30
6	150	6.84-7.60	174-193		\$313.50	\$536.80
6C	150	6.63-6.90	168-175		\$339.50	\$536.80
6-8	150-200	7.69-8.72	195-222		\$340.80	\$540.50
8A	200	8.63-9.05	219-229		\$344.30	\$554.20
8-10	200-250	8.54-10.10	217-257		\$353.20	\$578.50
10-12	250-300	10.64-12.12	270-308		\$391.20	\$608.70
12-14	300-350	12.62-14.32	321-364		\$421.50	\$656.20

HOW TO ORDER: Choose nominal pipe size x outlet size and thread configuration.

EXAMPLE: 4" Ductile Iron O.D. 4.80 with 3/4 CC outlet. Order 3415AS 4-5 x 3/4 CC.

Part Number: 3415040075HB-AS

NOTE: Please advise when saddles are being ordered for use on C900 pipe.

MANUFACTURER SUGGESTION: For PVC pipe applications, order saddle which has OD of pipe at the top of range.

OUTLET CODE PART CHART

Outlet	3/4		1		1 1/4		1 1/2		2		2 1/2		3		4	
Outlet size	075		100		125		150		200		250		300		400	
Thread standard	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	NPT	NPT	NPT	NPT	NPT
Outlet code	C	B	E	D	G	F	I	H	K	J	N	P	M			

IP = NPT CC=AWWA