



# 3417DI-PE

## DUCTILE IRON SADDLE WITH STRAPS

**BODY CASTING:** Ductile Iron per ASTM A536.

**STRAPS:** Type 304 (18-8) Stainless Steel per ASTM A240.

**STUD BOLTS:** Type 304 (18-8) Stainless Steel per ASTM A193.

**NUTS:** Type 304 (18-8) Stainless Steel per ASTM A194.

**NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and/or galling.

**GASKET:** NBR per ASTM D2000 with Unique dual O-Ring design permanently bonded in recessed casting, with a temperature range of -40°F to +248°F.

**FINISH:** Epoxy.



MEETS  
AWWA  
C230

Nominal Pipe Size	Letter	Pipe OD Range		Model 3417DI		Part number
				Outlet Size / List price		
Inches		Inches	MM	3/4 CC - 3/4 NPT 1 CC - 1 NPT	1 1/4 CC - 1 1/4 NPT 1 1/2 CC - 1 1/2 NPT 2 CC - 2 NPT	
2	A	2.38-2.50	61-64	\$325.30	\$337.30	3417+Nominal pipe size+Outlet size+H + Outlet Code+(-PE)
3	B	3.45-4.05	89-103	\$334.30	\$345.30	
4	A	4.00-4.50	102-114	\$370.70	\$390.70	
	B	4.74-5.63	120-143			
6	C	6.63-6.90	168-175	\$404.80	\$427.80	
8	C	8.63-9.05	219-229	\$584.30	\$610.40	
10	A	10.00-11.10	254-282	\$644.20	\$672.80	
12	A	12.00-13.20	305-335	\$705.90	\$738.10	

**HOW TO ORDER:** Choose nominal pipe size x outlet size and thread configuration. **Part Number:** 3417+Nominal pipe size+Outlet size+H + Outlet Code+(-PE), 341704B075HB-PE

**NOTE:** Please advise when saddles are being ordered for use on C900 pipe.

\*Available in 1.25 CC/NPT + 1.5 NPT.

Outlet	3/4"		1"		1 1/4"		1 1/2"		2"		2 1/2"
Outlet size	075		100		125		150		200		250
Thread standard	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT	CC	NPT
Outlet code	C	B	E	D	G	F	I	H	K	J	N

IP = NPT    CC=AWWA